



MANUAL BUTT FUSION WELDING MACHINE

WHDW2”M2 WHDW2”M4 WHDW4”M2 WHDW4”M4

Product Profile:

- High performance butt fusion welding machine equipment for PE, PP, PB & PVDF Pipes and fittings.
- Recommended for flow pressure up to 85 Psi.
- Complete machine consists of basic frame, facer, heater, carrying frame, clamping inserts, tool bag, screw driver and manufacturer’s test certificate.
- Suitable for working in trenches, on site and workshop.
- High Quality anti-stick PTFE coated heating plate with precision temperature control system.
- Highly portable, light weight, compact and user friendly.



Product Specifications

Model No.	WHDW2”M2	WHDW2”M4	WHDW4”M2	WHDW4”M4
Working Range	1 ¼ - 2”	1 ¼ - 2”	1 ¼ - 4”	1 ¼ - 4”
No. of Master Clamps	2	4	2	4
Maximum Heater Temperature	270 °C	270 °C	270 °C	270 °C
Input Voltage Requirements	220 V, 50/60Hz, 1Phase	220 V, 50/60Hz, 1Phase	220 V, 50/60Hz, 1Phase	220 V, 50/60Hz, 1Phase
Heater Power	0.7 KW	0.7 KW	1.6 KW	1.6 KW
Facer Power	0.7 KW	0.7 KW	0.8 KW	0.8 KW
Total Power	1.4 KW	1.4 KW	2.4 KW	2.4 KW
Reducer inserts (IPS)	1 ¼”, 1 ½”, & 2”	1 ¼”, 1 ½”, & 2”	1 ¼”, 1 ½”, 2”, 2 ½”, 3” & 4”	1 ¼”, 1 ½”, 2”, 2 ½”, 3” & 4”
Shipping Details	35KGS/ 0.32 CBM /1 Case	35KGS/ 0.32 CBM /1 Case	40KGS/ 0.32 CBM /1 Case	40KGS/ 0.32 CBM /1 Case